Figure: 16 TAC §9.140(f)

§9.140. Uniform Protection Standards

Table 1 (Revised February 2008)

ir	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	evisca i cornary 200		
Requirements	Self-service Dispenser Area	Storage Racks for DOT Portable or Forklift Containers	Licensee or Non- Licensee ASME 4001+ Gal. A.W.C.	Any Licensee Installation (DOT Container Filling and/or Service Station Only)
1. Red letters at least 2" high (or at	*	*	*	*
least 1 1/4" high for storage racks				
for DOT portable or forklift				
cylinders) on white or aluminum				
background: NO SMOKING				
			di.	
2. Red letters at least 4" high on			*	
white or aluminum background:				
WARNING FLAMMABLE GAS				
3. Black letters at least 4" high: NO			*	
TRESPASSING AUTHORIZED				
PERSONNEL ONLY				
4. Letters at least ½" high:	*			*
EXTINGUISH ALL PILOT				
LIGHTS AND OPEN FLAMES;				
VEHICLE MUST BE VACATED				
DURING FILLING PROCESS;				
TURN OFF ENGINE				
	*			
5. Letters at least 2" high on each	T			
operating side of the dispenser:				
PROPANE				
6. Block letters at least 2" high on a	*		*	*
background of contrasting color to				
the letters, including instructions on				
activation and visible from the point				
of transfer: PROPANE (or				
LP-GAS) EMERGENCY				
SHUTOFF				
7.Letters at least 4" high on		*	*	*
container or 1 1/4" high on cylinder				
exchange or storage rack indicating				
contents: LP-GAS or BUTANE or				
PROPANE and FLAMMABLE				
8. Letters at least 4" high on a			*	*
background of contrasting color to				
the letters, marked on both sides or				
both ends of any container holding				
unodorized gas: NOT ODORIZED				
			*	*
9. Letters at least 4" high: Name of			Ψ.	ጥ
Licensee (not required for				
nonlicensee installations)				
10. Letters at least 2" high on			*	*
operating end of container:				
W.P, WORKING PRESSURE, or				
WORKING PRESSURE, or				
WORK PRESS				
11. If more than one container,			*	*
letters at least 2" high on operating				
end of each container:				
CONTAINER NO. or				
TANK NO.				
<u> </u>	1		1	

12. Letters at least 2" high on a background of contrasting color, readily visible to the public, stating: 24-Hour Emergency Number (not required at non-licensee installations)	*	*	*	*
13. Lettering at least 3/4" high with the telephone number of the certified employee responsible for the outlet, and/or the operations supervisor, on a background of contrasting color, readily visible to the public (not required at nonlicensee installations)	*		*	*